



	Dimensions (LxWxH in mm)	Weight (gram)	Max thickness of fabric (mm)
Mini -	40 x 35 x 10	12.5	2
Midi -	70 x 40 x 18.5	20.0	6
Maxi -	75 x 38 x 18	35.0	3

Material specification

Produced in Sweden – from glass-fibre reinforced Nylon 6.
Holdon™ in white contains UV stabilizers. Holdon™ in colours other than white are protected from UV deterioration by pigment additives, causing UV blocking with the highest protection in black.

Standard colours available

Mini - white, green, blue, black, green, red, yellow.
Midi - white, black, blue.
Maxi - as for Mini Holdon™.

Temperature range

Minus 30 degrees Celcius to +100 degrees Celcius. Melting temperature +220 degrees Celcius

Median loading capacity

Mini - 70 kgs
Midi - 100 kgs
Maxi - 110 kgs

Median loading - explanation

Median loading capacity is determined by a series of separate static loadings applied to a single Holdon™ installed on a 680/700 gms/sq.mtr. vinyl fabric (without hem). The median loading capacity represents the approximate safe working load that can be applied to the Holdon™, and in general terms determines the safe load bearing capacity of the bridge within the sleeve component.

IMPORTANT – the median loading capacity does not represent the efficiency or holding/gripping power or efficiency of the Holdon™ - those elements of performance are determined by both the correct application of the Holdon™ and by the physical characteristics of the fabric/substrate onto which the Holdon™ is being applied.

Safety

The manufacturers and/or its distributors/agents make no claim whatsoever as to the holding/gripping efficiency or suitability of the Holdon™ clip and that the use of the product is the sole responsibility of the user(s).